



# B/Cp

## PLYWOOD

At CMPC we are committed to provide high quality products and offer an excellent service. That is why we have been developing SELEX PLYWOOD; a stable and reliable Plywood panel with high quality and amazing appearance.

- 100% Radiata Pine
- Easy to work with
- FSC<sup>®</sup> certified product



The mark of  
responsible forestry

\* Ask about our FSC<sup>®</sup> certified products.



Furniture and carpentry.



Concrete forming.

## PRODUCT BENEFITS AND APPLICATIONS

- Great dimensional stability.
- Excellent physical-mechanical resistance.
- Allows its use on both sides.

## FEATURES

	Selex B	Selex Cp
Finishing		
Sanding grade	150	150
Natural defects		
Sound	Up to 25 mm wide	Up to 40 mm wide
Unsound knots	Repaired, up to 25 mm wide	Repaired, up to 40 mm
Knots holes	Not allowed	Repaired, up to 25 mm
Pitch pockets	Up to 25 mm. wide	Allowed
Bark pockets	Not allowed	Allowed
Freckles	Allowed	Allowed
Machining defects		
Open splits	Up to 1 mm. wide	Up to 1 mm. wide
Open cracks	Up to 1 mm. wide	Up to 1 mm. wide
Fungal stains	Allowed	Allowed
Roughness	Allowed	Allowed
Repairs		
Inner splits in knots	Allowed	Unrepaired, up to 1 mm. wide
Routings with polyurethane	Occasionally	Up to 65 mm wide
Putty patches	Allowed	Allowed
Single wooden patches	Allowed	Allowed
Double wooden patches	Allowed	Allowed
Triple wooden patches	Allowed	Allowed

## GENERAL SPECIFICATIONS

Dimensions: 8' x 4' (2,440 x 1,220 m)	Thickness (mm)	6,5	9	12	15	18	21	25
	Thickness (inches)	1/4"	11/32"	15/32"	19/32"	23/32"	13/16"	1"
	N° of plies	3	3	5	5	6/7	7	9
Density	480 - 550 kg / m <sup>3</sup>							
Adhesive	Phenol - formaldehyde emission meet E1 standard .							
Structural Certification	PS1-22 by TP & EN 13986 (CE2+) by HFB .							
Moisture Content	8% to 12 % for all boards.							
Forestry Certification	FSC® certified product.							