



C/D

PLYWOOD

In CMPC we are committed to provide high quality products and offer an excellent service. That is why we have been developing SELEX PLYWOOD; a stable and reliable Plywood panel with high quality and amazing appearance.

- Consistent top quality.
- Easy to work with.
- 100% Radiata pine.
- FSC® certified product.



The mark of responsible forestry

* Ask about our FSC® certified products.



Partition walls, flooring, ceilings and sheathing.






Partition walls, Interior sheathing for walls and ceilings.



Packaging and transportation.

PRODUCT BENEFITS AND APPLICATIONS

-  Board intended for structural use in the construction area.
-  Easy handling due to their low weight - volume ratio.
-  It's high physical-mechanical bending, shear and compressive strength coupled with a production based on phenol-formaldehyde low emissivity (E1) resin, favor its use indoors and outdoors controlled with a high thermal insulation.

FEATURES

	Selex C	Selex D
Finishing		
Sanding grade	150	120
Natural defects		
Sound knots	Up to 40 mm. wide	Up to 65 mm. wide
Unsound knots	Up to 40 mm. wide	Up to 65 mm. wide
Knot holes	Up to 25 mm. wide	Up to 65 mm. wide
Pitch pockets	Allowed	Allowed
Bark pockets	Allowed	Allowed
Freckles	Allowed	Allowed
Machining defects		
Open cracks	Up to 25 mm. wide	Up to 25 mm. wide
Fungal stains	Allowed	Allowed
Roughness	Allowed	Allowed
Repairs		
Inner splits in knots	Not applicable	Not applicable
Routings with polyurethane	Not applicable	Not applicable
Putty patches	Not applicable	Not applicable

GENERAL SPECIFICATIONS

Dimensions: 4' x 8' (1,22 x 2,44 m)	Thickness (mm)	6,5	9	12	15	18	21	25
	N° of plies	3	3	5	5	6/7	7	9
Density	480 - 550 kg / m ³							
Adhesive	Formaldehyde emission meet E1 standard .							
Moisture Content	8% to 12% for all boards .							
Forestry Certification	FSC® Certified product.							