



C/D

NON STRUCTURAL

In CMPC we are committed to provide high quality products and offer an excellent service. That is why we have been developing SELEX PLYWOOD; a stable and reliable Plywood panel with high quality and amazing appearance.

- Consistent top quality.
- Easy to work with.
- 100% Radiata pine.
- FSC[®] certified product.



The mark of
responsible forestry

* Ask about our FSC[®] certified products.

PRODUCT BENEFITS AND APPLICATIONS



Has a variety of uses throughout the construction industry, particularly when structural characteristics are not required, whether that means not bearing weight or in cases where there is no requirement to meet the construction codes of Australia or New Zealand.

FEATURES

	Selex C	Selex D
Finishing		
Sanding grade	150	150
Natural defects		
Sound knots	Up to 40 mm. wide	Up to 65 mm. wide
Unsound knots	Up to 40 mm. wide	Up to 65 mm. wide
Knot holes	Up to 25 mm. wide	Up to 65 mm. wide
Pitch pockets	Allowed	Allowed
Bark pockets	Allowed	Allowed
Freckles	Allowed	Allowed
Machining defects		
Open cracks	Up to 25 mm. wide	Up to 25 mm. wide
Fungal stains	Allowed	Allowed
Roughness	Allowed	Allowed
Repairs		
Inner splits in knots	Not applicable	Not applicable
Routings with polyurethane	Not applicable	Not applicable
Putty patches	Not applicable	Not applicable

GENERAL SPECIFICATIONS

Dimensions: 4' x 8' (1,2 x 2,4 m)	Thickness (mm)	6,5	9	12	15	18	21	25
	Thickness (inches)	1/4"	11/32"	15/32"	19/32"	23/32"	13/16"	1"
	N° of plies	3	3	5	5	6/7	7	9
Density	480 - 550 kg / m ³							
Adhesive	Phenol-formaldehyde that complies with Super EO emission standard .							
Moisture Content	8% to 12% for all boards							
Forestry Certification	FSC® y PEFC certified product.							