



# PRIMED PLYWOOD

At CMPC, we are committed to providing high quality products and excellent service. That's why we have SELEX, a plywood panel with many advantages and high brand value, with the support and track record that only CMPC can offer.

- Primed with water-based products
- Ready for final painting
- 100% Radiata Pine



The mark of responsible forestry

\* Ask about our FSC® certified products.



## WHAT IS PRIMED PLYWOOD?

Primed Plywood is a Radiata Pine panel that has been primed with a water-based wood primer, ready to be installed in protected interiors and exteriors. It can also be painted later with a final finish.

## CHARACTERISTICS

- Colors: Black, gray, white and beige.
- Coated with primer (water-based, accepts further painting), with strong adherence and high covering power on the substrate.
- Features color consistency on all primed areas.
- Application of primer on 5 sides of the panel (face and edges).
- Oven-dried industrialized painting for a better result.
- FSC® certified product.
- Plywood option available with or without MCA impregnation treatment.

## ADVANTAGES

- Primed product (decreased costs and time).
- Ready for final application of paint, if needed.
- Accepts finishing paints well (top coat).
- Protected interior and exterior application.
- Provides a better surface finish.

## GENERAL SPECIFICATIONS

Dimensions: 4' x 8' (1.22 x 2.44 m) Width x Length	<b>Available Colors</b> Black, Gray and White	<b>Products</b>
	<b>Available Thicknesses</b> 6.5 mm, 9 mm, 12 mm, 15 mm, 18 mm, 21 mm and 30 mm 9 mm, 12 mm and 15 mm	Ply BC Smooth Ply BC Grooved (Sanded and Rustic)
Density	480 -550 kg/m2	
Moisture Content	8-12% for all types of panels	
Forest Certification	FSC® certified product	

## APPLICATIONS

- Protected interior and exterior cladding.
- Walls and partitions.
- Ceilings.

## CONSIDERATIONS

We recommend painting the panel with a high-quality water-based top coat within a maximum of 30 days after installation.


If you cut the panel, seal the edges before final installation.




Beige



White



Gray



Black