

B/C PLYWOOD

At CMPC we are committed to provide high quality products an offer an excellent service. That is why we have been developing SELEX PLYWOOD; a stable and reliable Plywood panel with high quality and amazing appearance.

- High visual appearance
- Special for decorative uses
- Consistent quality
- Easy to work with



* Ask about our FSC* certified products



Decoration and furniture.



Interior and exterior decorative sheathing for walls and ceilings.



Packaging, furniture and lamination.

PRODUCT BENEFITS AND APPLICATIONS

A multipurpose attractive quality panel.

Suitable for structural applications such as roofing, flooring and wall sheathing.

Easy to handle due to its excellent strength to weight ratio.

Outstanding visual face without open defects.

FEATURES

		秦沙斯			
	Selex B	Selex C			
Finishing					
Sanding grade	150	150			
Natural defects					
Sound knots	Up to 25 mm. wide	Up to 40 mm. wide			
Unsound knots	Repaired, up to 25 mm. wide	Up to 40 mm. wide			
Knot holes	Not allowed	Up to 25 mm. wide			
Pitch pockets	Up to 25 mm. wide	Allowed			
Bark pockets	Not allowed	Allowed			
Freckles	Allowed	Allowed			
Machining defects					
Open splits	Up to 1 mm. wide	Up to 25 mm. wide			
Open cracks	Up to 1 mm. wide	Up to 25 mm. wide			
Fungal stains	Allowed	Allowed			
Roughness	Allowed	Allowed			
Repairs					
Inner splits in knots	Allowed	Unrepaired, up to 1 mm. wide			
Routings with polyurethane	Occasionally	Not applicable			
Putty patches	Allowed	Not applicable			
Single wooden patches	Allowed	Not applicable			
Double wooden patches	Allowed	Not applicable			
Triple wooden patches	Allowed	Not applicable			

GENERAL SPECIFICATIONS

D: :	Thickness (mm)	6,5	9	12	15	18	21	25		
Dimensions: 8' x 4' (2,440 x 1,220 m)										
(2,440 x 1,220 m)	N° of plies	3	3	5	5	7	7	9		
Density	480 - 550 kg/m	1 ³								
Adhesive	CARB 2 and E1 compliant .									
Structural Certification	EN 13986-CE2 + (Structural), EN 636-2S, EN314-2 Class 3 .									
Moisture Content	8% to 12% for all boards.									
Forestry Certification	FSC® certified product.									