

# SIDING T1-24






- Special for decorative uses
- 100% Radiata Pine
- FSC<sup>®</sup> certified product



The mark of  
responsible forestry

\* Ask about our FSC<sup>®</sup> certified products.


## PRODUCT BENEFITS AND APPLICATIONS

-  Ideal for both interior and protected exterior use
-  Gives any Project a sophisticated and refined look
-  Has a multiple profiles available, offering suitable options for any Project
-  Comes with a shiplap that allows for precise installation
-  This profile has 24 grooves which have a width of 50 mm each

## FEATURES

	Selex Siding	C
Sanding grade	150	150
Solid face	✓	✗
Live Knots	✓	✓
Dead Knots	✗	✓
Routings with polyurethane	✗	✗
Putty patches	✓	✗
Wooden patches	Occasionally	✗

## PROFILES AVAILABLE



## GENERAL SPECIFICATIONS

Dimensions 4x8 (1,22 x 2,44 m)	Thickness (mm)	12
	Nº of plies	5
Density	480 – 550 kg / m³	
Adhesive	Europe: E1 and M1 (volatile organic compounds and low phenolformaldehyde emissions) / Australia: E super O	
Moisture content	8% to 12 % for all boards	
Forestry certification	FSC® certified product	



Interior Use



Interior Use



Decorative projects