



ROUGH SAWN

SIDING PLYWOOD

At CMPC we are committed to provide high quality products that create value for our customers. That is why we developed SELEX PLYWOOD; a stable and reliable Plywood panel with high quality and amazing appearance..

- 100% Radiata Pine
- Excellent appearance
- Suitable for decorative uses
- Easy to work with

SELEX ROUGH SAWN SIDING

Product benefits and applications

- Ideal for both interior and exterior use, Selex Rough Sawn Siding gives any project a sophisticated, refined look.
- Selex Rough Sawn Siding has multiple profiles available, offering suitable options for any project.
- Selex Rough Sawn Siding comes with a shiplap edge that allows for precise installation.

FEATURES



■ Solid face	✓	X
■ Live knots	✓	✓
■ Dead knots	X	✓
■ Routings with polyurethane	X	X
■ Putty patches	✓	X
■ Wooden patches	Occasionally	X

Grooving Options

Deep groove - 4"OC, 8"OC.

GENERAL SPECIFICATIONS

Dimensions: 4' x 8' (1,22 x 2,44 m)	Thickness (inches) 19/32	
	Thickness tolerances (inches)	min 0.578 max 0.609
	Number of veneers 5	
	Average panel weight	51.20 lbs
Density	29.96 - 34.26 Lbs / ft ³ (480 - 550 kg / m ³).	
Adhesive	CARB 2 compliant.	
Structural certification	ANSI/APA PRP 210 SIDING (15 mm).	
Forestry certification	FSC® certified product.	