products and offer an excellent service. That is why hace been developing SELEX PLYWOOD; a stable At CMPC we are committed to provide high quality and realiable Plywood panel with high quality and amazing appearance. Selex by cmpc

PRODUCT BENEFITS AND APPLICATIONS

- High quality visual panel, knot free, allowing the panel to be used for decorative applications, furniture making and flooting.
- → Easy to handle due to excellent weight-volume ratio.
- → CARB 2 compliant





		SELEX A	SELEX C	
FEATURES	FINISHING			
	Sanding grade	150	150	
	NATURAL DEFECTS			
	Sound knots	Not allowed	Up to 40 mm wide	
	Unsound knots	Not allowed	Up to 40 mm wide	
	Knot holes	Not allowed	Up to 25 mm wide	
	Pitch pockets	Up to 10 mm wide	Allowed	
	Bark pockets	Not allowed	Allowed	
	Freckles	Solid without restriction	Allowed	
	MACHINING DEFECTS			
	Open splits	Not allowed	Up to 25 mm wide	
	Open cracks	Not allowed	Up to 25 mm wide	
	Fungal stains	Slight	Allowed	
	Roughness	Slight	Allowed	
	REPAIRS			
	Inner splits in knots	Repaired, up to 1 mm wide	Unrepaired, up to mm wide	
	Routings with polyurethane	Very rarely	Allowed	
	Putty patches	Allowed	Not applicable	
	Single wooden patches	Occasional (up to 6)	Not applicable	
	Double wooden patches	Occasional (up to 3)	Not applicable	
	Triple wooden patches	Occasional (up to 2)	Not applicable	
Dimensions: 4' x 8' (1.22 x 2.44 m)	THICKNESS (MM)	6,5 9 12 15	18 21 25	
	N° OF PLIES	3 3 5 5	7 7 9	
	DENSITY	29.96 - 34.26 Lbs / ft ³ (480 - 550 kg		
	ADHESIVE	CARB 2 compliant		
	STRUCTURAL CERTIFICATION	P\$1-22 by TP & EN 13986 (CE2+) by HFB		
	MOISTURE CONTENT	8% to 12% for all boards.		
	FORESTRY CERTIFICATION	FSC® certified product		
	1	. 33 Sortinoa product		



CMPC products come from our own radiata pine plantations, carefully cultivated to produce the highest quality wood and certified by responsible forest management by FSC® and PEFC.



