

ROUGH SAWN SIDING

At CMPC we are committed to provide high quality products and offer an excellent service. That is why have been developing SELEX PLYWOOD; a stable and reliable Plywood panel with high quality and amazing appearance.


PRODUCT BENEFITS AND APPLICATIONS

- Ideal for both interior and exterior use, Selex Rough Sawn Siding gives any project a sophisticated, refined look.
- Selex Rough Sawn Siding has multiple profiles available, offering suitable options for any project.
- Selex Rough Sawn Siding comes with a shiplap edge that allows for precise installation.

Selex Siding



Selex C



		SELEX SIDING	SELEX C
FEATURES	Solid face	SI	NO
	Live knots	SI	SI
	Dead knots	NO	SI
	Routings with polyurethane	NO	NO
	Putty patches	SI	NO
	Wooden patches	Occasionally	NO
GROOVING OPTIONS		Deep groove - 4" OC, 8" OC.	
GENERAL SPECIFICATIONS	THICKNESS (IN)		19/32
	THICKNESS TOLERANCES (IN)		min 0.578 max 0.609
	NUMBER OF VENEERS		5
	AVERAGE PANEL WEIGHT		51.20 lbs
	DENSITY		29.96 - 34.26 Lbs / ft³ (480 - 550 kg / m³)
	ADHESIVE		CARB 2 compliant
	STRUCTURAL CERTIFICATION		ANSI/APA PRP 210 SIDING (15mm)
	FORESTRY CERTIFICATION		FSC® certified product
	Dimensions: 4' x 8' (1.22 x 2.44 m)		

Dimensions:
4' x 8' (1.22 x 2.44 m)

CMPC products come from our own radiata pine plantations, carefully cultivated to produce the highest quality wood and certified by responsible forest management by FSC® and PEFC.



Scan for more information

